

EUROTILES

PAVING THE NATION



Sunway Pyramid, New Wing, Selangor



CABANA

THE NATURAL BEAUTY OF CHIPPED STONE



CA-M1-105



CA-M1-601

FLORANA

— AN ATTRACTIVE AVENUE TO TREAD
— COLOR PIGMENTED FINISH



FL-M8-N00



FL-M5-P05

TOFANA

— PAVING FOR TODAY'S URBAN HABITAT
— HONED (GRIND) FINISH



TO-M2-202-N05



TO-M4-701-N15

FONTANA

— LASTING IMPRESSIONS WITH EVERY STEP
— SHORT-BLASTED FINISH



FO-M7-P02L



FO-M1-N03

DUAL FINISH

— THE FINISHING TOUCH BENEATH
— SHORT BLASTED & HONED FINISH



DF-M10-204-P02



DF-MIQ-203-N00

VISUALLY IMPAIRED SLABS

MORE THAN SURFACE BEAUTY



FL-M33-P02



FL-M32-P02

SPECIFICATIONS

Cabana, Fontana & Florana

Dimension (mm) 400 X 400	Dimension (mm) *500 x 500	Dimension (mm) *400 x 600
Thickness (mm) 40	Thickness (mm) 50	Thickness (mm) 40
Coverage (pcs/m²) 6.25	Coverage (pcs/m²) 4.00	Coverage (pcs/m²) 4.16

Tofana

Dimension (mm) *300 X 300	Dimension (mm) 400 x 400	Dimension (mm) *400 x 600
Thickness (mm) 28	Thickness (mm) 40	Thickness (mm) 40
Coverage (pcs/m²) 11.11	Coverage (pcs/m²) 6.25	Coverage (pcs/m²) 4.16

Visually Impaired Slabs

Dimension (mm) *300 X 300	Dimension (mm) 400 x 400	* on-standard sizes are subject to a minimum quantity of 3000m ² per order.
Thickness (mm) 28	Thickness (mm) 40	
Coverage (pcs/m²) 11.11	Coverage (pcs/m²) 6.25	

Dual Finish

Dimension (mm) 400 x 400	These specifications set out the requirements for compressed concrete paving slabs. They are recommended for use in public areas which are subject to pedestrian and light vehicular traffic.
Thickness (mm) 40	
Coverage (pcs/m²) 6.25	

RAW MATERIALS USED

- **Cement**
 - Ordinary Portland Cement - MS 522 : 2003
 - White Portland Cement - MS 888 : 1991
- **Colour Pigment** - Colour pigment: BS 1014
- **Aggregates** - 5 mm aggregates: BS 882
- **Sand** - Washed: BS 1119
- **Additives** - To the manufacturer's requirement

PHYSICAL PROPERTIES

- **Tolerance**
The tolerance of any single paving slab may be
 - Cabana/Dual Finish ± 5mm
 - Visually Impaired Slabs/Florana ± 5mm
 - Fontana/Tofana ± 5-10mm

- **Length and Width**

The length and width of any single paving slab may be within 1.5mm of the specified dimensions

- **Colour**

The colour configuration shall conform as close as practicable to the "sample batch" colour

- **Transverse Strength**

The minimum 28 days transverse strength may be 4N/mm²

- **Water Absorption**

Water absorption on paving slab surface may be less than 0.4g/cm², while total absorption may be less than 8%

- **Compressive Strength**

45 MPA (Tested on 100mm X 100mm X 40mm cut sample)

- **Skid Resistance - 65**

(Except for Tofana Series)

SPECIFICATION

- Complied with MS738 : 1981 specification for Terrazzo floor tiles

FEATURES

- Natural stone chipping and pebble finish
- Various and imported colour stone chippings (upon request)
- Blends with nature
- Shot-blasted finish
- Granolithic finish
- Colour pigmented finish
- Large range of facial designs
- Honed (Grind) finish
- Low maintenance
- Durable and non-slip surface

APPLICATIONS

- Pool decks
- Park and garden landscapes
- Patios
- Pedestrian malls
- Driveways
- Walkways


EFFLORESCENCE (Secondary)

This superficial phenomenon is commonly found in most concrete-based or cementitious products. However, this efflorescence effect may disappear over time (weathering) whereby rain usually washes the efflorescence away in about six months to a year and in the worst scenario could take up to two years.


Note : Finished product colour may vary, subject to the colour of sand, cement and colour pigments used at the time of production.

INSTALLATION METHODS

CEMENT MORTAR METHOD



SAND BEDDING METHOD



Basecourse thickness is subject to soil investigation that includes CBR soil test, sub-base and subgrade soil conditions and Consultant's recommendation.



T: 08 9249 9988
F: 08 9249 1155
M: 0433 190 436

Head Office: 47 Resource Way, Malaga WA 6090
Postal Address: PO Box 3364, Malaga DC WA 6945
Email: ian@acphardstand.com

ACP
HARDSTAND SOLUTIONS
is an Agent for:

SUNWAY
BUILDING
MATERIALS

SUNWAY PAVING SOLUTIONS SDN BHD
(77490-W)

E-mail: spsales@sunway.com.my www.sunwaypavingsolutions.com
Facebook: www.facebook.com/sunwaypavingsolutions